

SMD Crystal Oscillators

CMOS Output

7.0x5.0x1.3mm O75 Series



Features

- Small SMD seam sealed clock crystal oscillator units.
- High precision characteristic covering up to wide frequency range.
- Designed for automatic mounting and reflow soldering.
- Tri-State function available.
- Supply voltage range : 1.8 V~5.0 V.
- High stability, low jitter, low power consumption.
- Main application :wireless communication, PC, and LCDM.
- RoHS Compliant / Pb Free.



Crystals specifications

ITEMS/TYPE	O75		
Frequency Range	1~170MHz		
Output Type	CMOS		
Output Load	15pF, 30pF, or specify		
Oscillation Mode	Fundamental / 3rd Overtone		
Supply Voltage	1.8V	2.5V,2.8V,3.3V	5V
Frequency Stability	± 20 ppm , or specify		
Operating Temperature Range	-40~+85 °C , or specify		
Storage Temperature Range	-55~+125 °C		
Voltage Vol (Max.)/Voltage Voh (Min.)	VOH=90%Vdd / VOL+10%Vdd		
Rise (Tr) / Fall (Tf) Time	8ns Max.		
Current Consumption	20mA Max.		
Symmetry	45~55%		
Start-up Time	5ms Max.		
Phase Jitter(12KHz~20MHz)	1ps Max.		
Aging (at 25°C)	± 3 ppm / year Max.		
Packing Unit	1,000pcs/Reel		

Dimensions and patterns(unit:mm)

